

Single column industrial platforms

Alapont **single column industrial platforms** are designed to **lift loads from 150kg to 3,000kg**.

They have a wide range of dimensions, routes and stops. In addition, there are models that incorporate an inverted chassis that allows the platform, as well as its guides, to be flush with the last floor level.

All Alapont Logistics industrial forklift platforms are manufactured under the European directive 98/371 / CE and applicable national standards.



Load (kgs)	(I) Width (mm)		(G) Deep (mm)		A (mm)			F (mm)	L (mm)	Flight (Min)	Reacc. (kgs)
	Max	Min	Max	Min	PRH-1	PRH-1(2)	PRH-1-1				
150	1200	550	900	500	100	/	750	120	430	1340	1000
300	1500	750	1300	600	210	/	750	155	610	1500	1400
400	1500	750	1300	600	210	/	750	155	610	1500	1600
500	2000	950	1300	600	210	450	900	155	805	1560	1800
750	2500	950	1500	800	210	550	1000	180	805	1560	2200
1000	2700	1150	2000	800	250	550	1000	205	1000	1800	2800
1500	3000	1150	2000	800	270	650	1250	230	1000	1980	3400
2000	3500	1650	2000	1000	280	650	1500	230	1000	2000	4200
3000	3200	1650	2000	1000	/	650	1500	235	1500	2000	5900

Technical description

- ✓ **Custom manufactured** for various heights of travel and surface areas.
- ✓ Maximum **travel height – 12 metres**.
- ✓ **Non-slip plate**.
- ✓ Cable slack or **breakage control**.

- ✓ **Hydraulic fall arrest**.
- ✓ **Nominal speed 0.1 m/s** (option of a 0.2 m/s model) plus end of travel safety timer.
- ✓ **Button pads** with emergency stop button, located outside the platform's footprint.